



**THE  
FLOORING  
LAB**

# Adore Collection



LIVINSAFE A+

## Technical Data

|                           |                                                       |                 |                                 |
|---------------------------|-------------------------------------------------------|-----------------|---------------------------------|
| Type                      | Engineered Timber - European Oak                      | Finish          | Matte                           |
| Plank Thickness           | 14mm                                                  | Surface         | Smooth/Brushed                  |
| Dimensions                | 840mm (L) x 120mm (W)                                 | Wear Layer      | 3mm                             |
| Planks per Box            | 12                                                    | Substrate Layer | Heavea Core                     |
| M <sup>2</sup> per Box    | 1.2096 m <sup>2</sup>                                 | Backing Layer   | Sengon                          |
| M <sup>2</sup> per Pallet | 48.3840 m <sup>2</sup> (S) 96.7680 m <sup>2</sup> (L) | Profile         | Bevel                           |
| Decors                    | 6                                                     | Coating Sysytem | Water Based UV Hardened Coating |
| Installation method       | T&G Floating / Direct Stick                           | Grade           | TrueFeature EU                  |

## Performance

|                  |                                          |          |                    |
|------------------|------------------------------------------|----------|--------------------|
| Abrasion Rating  | ≥ 5000                                   | Standard | ASTM D 4060-CS17   |
| Gloss Value      | 4% ±2%                                   |          | ISO 2813           |
| Moisture Content | 7% ±2%                                   |          | EN 13183-1         |
| Fire Rating      | CHF 3.8kW/m <sup>2</sup> - Smoke 27%.min |          | AS ISO 9239.1-2003 |
| Slip Resistance  | P3                                       |          | AS 4586:2013       |

## Environmental

|                     |                                |          |                 |
|---------------------|--------------------------------|----------|-----------------|
| VOC Rating          | E1                             | Standard | ASTM D5116      |
| Veneer              | FSC Certificate SCS-COC-008306 |          | FSC-STD-40-004  |
| Substrate / Backing | SVLK/FLEGT                     |          | Indonesian TLAS |

## Warranty

|              |                                  |             |                                                      |
|--------------|----------------------------------|-------------|------------------------------------------------------|
| Residential: | Lifetime Structural / 25YearWear | Commercial: | On Application   <a href="#">Click Here to Apply</a> |
|--------------|----------------------------------|-------------|------------------------------------------------------|



Bevel Edge



Tongue & Groove




Hevea Core




3mm Wear Layer




Ivory




Sunflower




Raven



Cinder



Pure Diamond



Ethereal