THE FLOORING LAB

PRODUCT SPECIFICATION

ADORE COLLECTION - HERRINGBONE

Technical Data			
Туре	Engineered Timber - European Oak	Finish	Matte
Plank Thickness	14.2mm	Surface	Smooth/Brushed
Dimensions	840mm (L) x 120mm (W)	Wear Layer	3.2mm
Planks per Box	12	Substrate Layer	Heavea Core
M ² per Box	1.2096 m ²	Backing Layer	Spruce
M ² per Pallet	48.3840 m ² (S) 96.7680 m ² (L)	Profile	Bevel
Decors	6	Coating Sysytem	Water Based UV Hardened Coating
Installation method	T&G Floating / Direct Stick	Grade	Lifestyle (ABCD)
Performance		Standard	
Abrasion Rating	≥ 5000	ASTM D 4060-CS17	
Gloss Value	4% ±2%	ISO 2813	
Moisture Content	7% ±2%	EN 13183-1	
Acoustic	ТВА	ISO140/ISO717.2	
Fire Rating	ТВА	ISO92939-1	
Slip Resistance	Р3	AS4586	
Environmental		Standard	
VOC Rating	E1	ASTM D5116	
Accreditation	Certified	ISO14001	
	FSC & PEFC (Available On Request)		

LIFE

Warranty

wairancy					
Residential:	Lifetime Structura	. / 25YearWear	Commercial:	On Application	
				and the second	
					IN
		\leq \leq $<$ $<$			
	\bigcirc \subset	$\overline{}$	$ \rightarrow \bigcirc $		\mathbf{O}
Water Based UV He	evea Core 3.2n	nm Beve	el Edge Tongue & Groc	ove Lifestyle Grade	Direct Stick
ardened Coatings	Wearl	ayer			
The second s			10		The Martine
and the second second					S
and the second second	Contraction of the second seco		and the		
The second way				a start and the	
1					
	and the second				
Pure Diamond	Sunflower	Copper	Dark Chocolate	Blonde	Ash