



PRODUCT SPECIFICATION

FLOOR ART COLLECTION (190x14/3)

Technical Data

Type	Engineered Timber - European Oak	Finish	Matte
Plank Thickness	14mm	Surface	Smooth / Brushed
Dimensions	2130mm (L) x 190mm (W)	Wear Layer	3mm
Planks per Box	6 (Nested Boards)	Substrate Layer	Heavea Core
M ² per Box	2.4282 m ²	Backing Layer	Spruce
M ² per Pallet	133.351 m ² (S) 160.261 m ² (L)	Profile	Bevel
Decors	8	Coating System	Water Based UV Hardened Coating
Installation method	T&G Floating / Direct Stick	Grade	Lifestyle (ABCD)

Performance

Abrasion Rating	≥ 5000	Standard	ASTM D 4060-CS17
Gloss Value	4% ±2%		ISO 2813
Moisture Content	7% ±2%		EN 13183-1
Acoustic	TBA		ISO140/ISO717.2
Fire Rating	TBA		ISO92939-1
Slip Resistance	TBA		AS4586

Environmental

VOC Rating	E1	Standard	ASTM D5116
Accreditation	Certified PEFC (Available On Request)		ISO14001

Warranty

Residential:	Lifetime Structural / 25YearWear	Commercial:	On Application
--------------	----------------------------------	-------------	----------------



Water Based UV Hardened Coatings



Hevea Core



3mm Wear Layer



Bevel Edge



Tongue & Groove



Lifestyle Grade



Direct Stick




Seine



Missouri



Loire



Orinocco



Tuscany



Rhone



San Marco



Rio Grande



PRODUCT SPECIFICATION

FLOOR ART COLLECTION (240x14/3)

Technical Data

Type	Engineered Timber - European Oak	Finish	Matte
Plank Thickness	14mm	Surface	Smooth / Brushed
Dimensions	2130mm (L) x 240mm (W)	Wear Layer	3mm
Planks per Box	6 (Nested Boards)	Substrate Layer	Heavea Core
M ² per Box	3.0672 m ²	Backing Layer	Spruce
M ² per Pallet	101.218 m ²	Profile	Bevel
Decors	4	Coating System	Water Based UV Hardened Coating
Installation method	T&G Floating / Direct Stick	Grade	Lifestyle (ABCD)

Performance

Abrasion Rating	≥ 5000
Gloss Value	4% ±2%
Moisture Content	7% ±2%
Acoustic	TBA
Fire Rating	TBA
Slip Resistance	TBA

Standard

ASTM D 4060-CS17
ISO 2813
EN 13183-1
ISO140/ISO717.2
ISO92939-1
AS4586

Environmental

VOC Rating	E1
Accreditation	Certified PEFC (Available On Request)

Standard

ASTM D5116
ISO14001

Warranty

Residential:	Lifetime Structural / 25YearWear	Commercial:	On Application
--------------	----------------------------------	-------------	----------------



Water Based UV Hardened Coatings



Hevea Core



3mm Wear Layer



Bevel Edge




Tongue & Groove



Lifestyle Grade



Direct Stick



Absolute



Jungfrau



Bergen



Mauritius

THE FLOORING LAB



PRODUCT SPECIFICATION

FLOOR ART COLLECTION (190x20/6)

Technical Data

Type	Engineered Timber - European Oak	Finish	Matte
Plank Thickness	20mm	Surface	Smooth
Dimensions	2130mm (L) x 190mm (W)	Wear Layer	6mm
Planks per Box	4 (Nested Boards)	Substrate Layer	Heavea Core
M ² per Box	1.6188 m ²	Backing Layer	Spruce
M ² per Pallet	89.034 m ²	Profile	Bevel
Decors	4	Coating System	Water Based UV Hardened Coating
Installation method	T&G Floating / Direct Stick	Grade	Lifestyle (ABCD)

Performance

Abrasion Rating	≥ 5000
Gloss Value	4% ±2%
Moisture Content	7% ±2%
Acoustic	TBA
Fire Rating	TBA
Slip Resistance	TBA

Standard

ASTM D 4060-CS17
ISO 2813
EN 13183-1
ISO140/ISO717.2
ISO92939-1
AS4586

Environmental

VOC Rating	E1
Accreditation	Certified PEFC (Available On Request)

Standard

ASTM D5116
ISO14001

Warranty

Residential:	Lifetime Structural / 25YearWear	Commercial:	On Application
--------------	----------------------------------	-------------	----------------



Water Based UV Hardened Coatings



Hevea Core



6mm Wear Layer



Bevel Edge




Tongue & Groove




Lifestyle Grade




Direct Stick



Absolute



Polos



Rhodes



Majorca