## THE FLOORING LAB

## PRODUCT SPECIFICATION

## ADORE COLLECTION - HERRINGBONE

Technical Data				
Туре	Engineered Timber - European Oak	Finish	Matte	
Plank Thickness	14.2mm	Surface	Smooth/Brushed	
Dimensions	840mm (L) x 120mm (W)	Wear Layer 3.2mm		
Planks per Box	12	Substrate Layer Heavea Core		
M² per Box	1.2096 m <sup>2</sup>	Backing Layer Spruce		
M² per Pallet	48.3840 m <sup>2</sup> (S) 96.7680 m <sup>2</sup> (L)	Profile	Bevel	
Decors	6	Coating Sysytem	Water Based UV Hardened Coating	
Installation method	T&G Floating / Direct Stick	Grade	Lifestyle (ABCD)	
Performance		Standard		
Abrasion Rating	≥ 5000	ASTM D 4060-CS17		
Gloss Value	4% ±2%	ISO 2813		
Moisture Content	7% ±2%	EN 13183-1		
Fire Rating	CHF 3.8kW/m <sup>2</sup> - Smoke 27%.min	AS ISO 9239.1-2003		
Slip Resistance	P3	AS 4586:2013		
Environmental		Standard		
VOC Rating	E1	ASTM D5116		
Accreditation	Certified	ISO14001		
	FSC & PEFC (Available On Request)			

WARRAND E

Warranty						
Residential:	Lifetime St	Lifetime Structural / 25YearWear		Commercial:	On Application   <u>Click Here to Apply</u>	
	and a start of the second		1-12-12-12-1			
0	0	A	-	0		en la
UV		(54)				
	U	$\overline{}$	$\mathbf{r}$			
Water Based UV	Hevea Core	3.2mm	Bevel Edge	Tongue & Groove	Lifestyle Grade	Direct Stick
Hardened Coatings	1.6. 1.	Wear Layer	A starter	and the second second	and the second second	
and the state	The Company					5
and the second second	"COALL"	- A Carton		and the		
					- Carlos and	and the second se
the state of the state		The second				
Pure Diamond	Sunflower	Copper	Dark	Chocolate	Blonde	Ash